

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/021028 A1

(51) International Patent Classification⁷: **G01R 33/563**,
A61B 5/026, 5/055

(74) Agent: KOCOVSKY, Thomas, E.; Fay, Sharpe, Fagan,
Minnich & McKee, LLP, 1100 Superior Avenue, Seventh
Floor, Cleveland, OH 44114-2579 (US).

(21) International Application Number:
PCT/US2003/026580

(22) International Filing Date: 26 August 2003 (26.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/406,040 27 August 2002 (27.08.2002) US

(71) Applicant (for all designated States except US):
KENNEDY KRIEGER INSTITUTE [US/US]; 707
North Broadway, Baltimore, MD 21205 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicants and


(72) Inventors: **VAN ZIJL, Peter, C., M.** [NL/US]; 7712 Mill-
stone Ct., Ellicott City, MD 21043 (US). **LU, Hanzhang,**
(nmi) [CN/US]; 4403 Falls Bridge Dr., Apt. F, Baltimore,
MD 21211 (US). **GOLAY, Xavier,** (nmi) [CH/US]; 1129
William Street, Baltimore, MD 21230 (US).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: MICROVASCULAR BLOOD VOLUME MAGNETIC RESONANCE IMAGING



(57) Abstract: A magnetic resonance imaging system includes a magnetic resonance imaging scanner (10) that performs an inversion recovery magnetic resonance excitation sequence (70) having a blood-nulling inversion time (60) determined based on a blood TI value appropriate for a selected magnetic field and blood hematocrit, whereby magnetic resonance of blood is substantially nulled. The inversion recovery excitation sequence (70) includes an inversion radio frequency pulse (74) applied with a small or zero slice-selective magnetic field gradient pulse to avoid inflow effects, and an excitation radio frequency pulse (80). The inversion pulse (74) and excitation pulse (80) are separated by the inversion time (60). The magnetic resonance imaging scanner (10) subsequently performs a readout magnetic resonance sequence (72) or spectroscopy sequence to acquire a magnetic resonance signal from tissue other than the nulled blood. A reconstruction processor (44) generates a reconstructed image from the acquired magnetic resonance signal.

WO 2004/021028 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

MICROVASCULAR BLOOD VOLUME MAGNETIC RESONANCE IMAGING

Background of the Invention

The following relates to the diagnostic imaging arts. It finds particular application in non-invasive measurement by magnetic resonance imaging of cerebral blood volumes, and will be described with particular reference thereto. However, it also finds
5 application in measurement by magnetic resonance imaging of blood volumes in other tissues.

In-situ measurement of blood volume is useful in various clinical, diagnostic, and research applications. Local cerebral blood volume changes, for example, correlate with local neuronal activity in the brain. Cerebral blood volume measurements during physiological stimulation thus provides a tool for functional studies of brain activity. Cerebral blood volume
10 measurements can also provide information about impaired and/or damaged tissue in stroke victims, as well as about lesions in many disorders, including, but not limited to cancer, vascular disorders, and the like. Blood volume imaging of other organs besides the brain can similarly provide functional and diagnostic data that is useful in clinical studies, diagnoses, and tests (e.g. stress tests or tests of vascular compliance).

Various imaging modalities have been used to measure blood volume characteristics, including positron emission tomography, single photon emission computed tomography, and magnetic resonance imaging. Most of these are invasive approaches, in which the subject is administered a suitable contrast agent that selectively enhances blood contrast in the selected imaging modality. For magnetic resonance imaging, various paramagnetic contrast
15 agents are commonly used for this purpose. The requirement of an administered contrast agent is a substantial disadvantage of these techniques.

Magnetic resonance imaging of blood oxygenation level dependence (BOLD) is a non-invasive technique for indirectly measuring blood volume. In this technique, blood hemoglobin is used as an endogenous contrast agent. In one BOLD imaging approach,
25 magnetic resonance imaging is performed as a function of physiological stimulation that causes changes in blood oxygenation level. Blood volume is estimated from BOLD measurements by making assumptions pertaining to other parameters that affect blood oxygenation level, such as blood flow. Hence, BOLD does not provide a direct measure of the blood volume.

A disadvantage of both the invasive techniques and the BOLD techniques as
30 applied to blood volume measurement is that these existing techniques generally do not differentiate between blood in large blood vessels, on the one hand, and perfused blood in

small capillaries or other microvessels, on the other hand. The blood volume in larger blood vessels is principally controlled by sympathetic regulation. In contrast, blood volume in microvessels having typical diameters of less than about 200 microns tends to vary to maintain local homeostasis or in response to chemicals such as vasodilators or vasoconstrictive compounds. Consequently, the blood volume of microvessels responds to physiological perturbations such as local neuronal activity. For functional magnetic resonance imaging, the volume of blood in the microvessels is typically of principle interest, while the blood signal from larger blood vessels is interfering and thus undesirable. On the other hand, total microvascular plus macrovascular blood volume may change in some diseases, including but not limited to for instance arteriovenous malformations.

The present invention contemplates an improved apparatus and method that overcomes the aforementioned limitations and others.

Brief Summary of the Invention

According to one aspect, a magnetic resonance imaging method is provided. A blood-nulling magnetic resonance excitation sequence is performed that substantially nulls a magnetic resonance signal from blood. Subsequent to the performing of the blood-nulling magnetic resonance excitation sequence, a readout magnetic resonance sequence is performed to acquire a magnetic resonance signal from tissue other than the nulled blood.

According to another aspect, a magnetic resonance system is disclosed. A blood nulling means is provided for performing a blood nulling magnetic resonance excitation sequence that substantially nulls a magnetic resonance signal from blood. A readout means is provided for performing a readout magnetic resonance sequence to acquire a magnetic resonance signal from tissue other than the nulled blood, the readout means operating subsequent to operation of the blood nulling means.

One advantage resides in measuring the parenchymal vascular space occupancy, which is more sensitive to physiological perturbations than is the total vascular volume which includes the large blood vessels.

Another advantage resides in providing measurements of the absolute blood volume.

Yet another advantage resides in providing images with substantially nulled blood magnetic resonance signal, i.e. a blood signal reduction sufficient to have MRI signal remaining that is predominantly from other tissues.

Numerous additional advantages and benefits will become apparent to those of ordinary skill in the art upon reading the following detailed description of the preferred embodiments.

Brief Description of the Drawings

The invention may take form in various components and arrangements of components, and in various process operations and arrangements of process operations. The drawings are only for the purpose of illustrating preferred embodiments and are not to be construed as limiting the invention.

FIGURE 1 diagrammatically shows a magnetic resonance imaging system for measuring vascular space occupancy.

FIGURE 2 diagrammatically shows a magnetic resonance imaging pulse sequence employing inversion recovery to null the blood signal. In FIGURE 2, the time intervals TI, TE, TR are not drawn to scale.

FIGURE 3 shows a block diagram of a processor for computing a blood volume at rest and a blood volume change occurring responsive to a physiological perturbation.

FIGURE 4 shows a block diagram of a processor for computing absolute blood volume using a reconstructed image acquired with the blood signal nulled by an inversion recovery preparation.

FIGURE 5 shows a block diagram of a processor for computing a difference image having enhanced contrast for vascular space occupancy abnormalities.

Detailed Description of the Preferred Embodiments

With reference to FIGURE 1, a magnetic resonance imaging scanner 10 includes main magnet coils 12, which are preferably superconducting coils, although resistive main magnet coils or a permanent magnet can also be employed. The main magnet coils 12 are energized to generate a substantially uniform main magnetic field in an examination region 14. Magnetic field gradient coils 16 produce gradients in selected spatial directions to spatially encode magnetic resonances that are generated by energizing a radio frequency coil 18. In FIGURE 1, a whole-body radio frequency coil 18 is shown; however, local coils such as head coils, phased radio frequency coil arrays, SENSE coils, and the like can be used instead of or in conjunction with the whole-body radio frequency coil 18 to excite magnetic resonances and/or to detect magnetic resonance echoes.

A magnetic resonance sequence controller 30 coordinates and controls a radio frequency transmitter 34 that is coupled to the whole-body radio frequency coil 18 or another radio frequency coil to excite magnetic resonance echoes, and controls magnetic field gradient controllers 32 coupled to the gradient coils 16 to spatially encode the excited magnetic resonance echoes. One or more radio frequency receivers 36 coupled to the whole-body radio frequency coil 18 or another radio frequency coil detects, demodulates, and digitizes the magnetic resonance echoes and stores digital magnetic resonance samples in a k-space memory

40. A reconstruction processor 44 performs a Fourier transform-based image reconstruction or other type of image reconstruction to generate one or more reconstructed images from the stored k-space magnetic resonance samples.

The reconstructed images are stored in an image memory 46, processed by a
5 video processor 50 and displayed on a user interface 52, transmitted over a local computer network or the Internet, or otherwise processed. Preferably, the user interface 52 includes a display, printer, or other output device that allows a radiologist or other operator to view, render, or otherwise manipulate the reconstructed images. Moreover, the user interface 52 preferably enables the radiologist or other operator to communicate with the magnetic
10 resonance sequence controller 30 to create magnetic resonance imaging sequences, modify imaging sequences, execute imaging sequences, or otherwise control the magnetic resonance imaging scanner 10.

With continuing reference to FIGURE 1, for clinical or diagnostic applications in which the blood volume is of interest, a measure of the vascular space occupancy (VASO) is
15 performed. The approach uses an inversion recovery magnetic resonance excitation sequence having an inversion time 60 optimized for substantial nulling of the blood signal based on a blood T1 value particular to a certain magnetic field strength and hematocrit range. The inversion recovery magnetic resonance excitation sequence substantially nulls the signal from blood so that the magnetic resonance signal corresponds predominantly to tissue, with
20 substantially negligible contribution of blood. This approach takes advantage of a substantial independence of the T1 value of blood on blood oxygenation, which allows the inversion recovery blood nulling to be operative for different types of vessels (arterial, arteriolar, capillary, venular, and venous) as well as throughout a physiological perturbation cycle.

A suitable value for the inversion time (TI) 60 for nulling blood can be
25 obtained in a number of ways. In one suitable approach, a blood T1 measuring sequence 62 is applied by the sequence controller 30 to measure a T1 value of a representative blood sample using a blood perfusion apparatus, and the inversion time (TI) 60 is computed therefrom. Alternatively, a major blood vessel can be identified in a reconstructed image, and a direct measurement of the T1 value of blood inside the identified blood vessel is obtained using
30 conventional magnetic resonance imaging sequences. In another approach, as it has been found in practice that the T1 of blood is generally not subject-dependent for most human subjects having substantially normal blood, suitable inversion times (TI) can be computed from measurements of a representative blood sample of substantially normal human blood or of animal blood of suitable mammalian origin and collected in a table 64, such as Table I and
35 Table II contained herein. These values are generally suitable for substantially normal human blood, and include inversion time dependence upon the main magnetic field strength (Table I

providing values for a 1.5T field, and Table II providing values for a 3.0T field) and on the sequence repeat time (TR). Rather than employing tabulated data, the inversion time 60 can be related to magnetic field strength, repeat time TR, and optionally other parameters by an empirical functional relationship or other suitable relationship. The tabulated TI values are preferably used as a guideline for determining an inversion time TI that substantially nulls blood so that signals are predominantly from tissue. The tabulated values do not exclude other TI values that can also accomplish blood nulling.

TR (ms)	optimal TI (ms)	remaining gray signal
1000	409.4499457	0.039848653
1500	551.5765181	0.07104825
2000	659.2454703	0.100852361
2500	738.9402994	0.126845436
3000	796.8489702	0.148292976
3500	838.3345867	0.165337186
4000	867.7421743	0.178518564
4500	888.427932	0.188505318
5000	902.8982691	0.195951912
5500	912.9810254	0.20143462
6000	919.987164	0.205430439
6500	924.8460607	0.208318508
7000	928.2112602	0.21039169
7500	930.5397637	0.21187148
8000	932.1498927	0.212922716
8500	933.262774	0.213666531
9000	934.0317304	0.214191053
9500	934.5629341	0.214559874

Table I – Optimal inversion times (TI) for blood at 1.5 Tesla magnetic field

TR (ms)	optimal TI (ms)	remaining gray signal
1000	424.6207165	0.029639854
1500	583.5056824	0.054873106
2000	711.232168	0.080671988
2500	812.0982526	0.1047927
3000	890.5574158	0.126155559
3500	950.8320255	0.144394456
4000	996.6759107	0.159557069
4500	1031.270597	0.171909777
5000	1057.21771	0.18181485
5500	1076.588295	0.189656765
6000	1090.998208	0.195801064
6500	1101.689382	0.20057404
7000	1109.605744	0.204255213
7500	1115.458796	0.207077192
8000	1119.781556	0.209229423
8500	1122.971521	0.210863669
9000	1125.324122	0.212099926
9500	1127.058395	0.21303208

Table II – Optimal inversion times (TI) for blood at 3.0 Tesla magnetic field

An inversion time adjustment is optionally performed to compensate for deviations in blood T1 value resulting from abnormal hematocrit values, sickle-cell pathologies, or another blood abnormality of a specific imaging subject. In one suitable adjustment technique, the blood-nulling inversion recovery imaging sequence is performed for several inversion times around the blood nulling inversion time selected from Tables I and II, and the blood nulling inversion time 60 is selected as the inversion time providing substantially negligible image signal from a large blood vessel. A data flow line 66 in FIGURE 1 corresponds to selecting the blood nulling inversion time 60 based on magnetic resonance measurements performed using the scanner 10.

FIGURE 2 diagrammatically shows a suitable magnetic resonance imaging pulse sequence employing a blood-nulling inversion recovery magnetic resonance excitation sequence 70 to null the blood signal, and an exemplary single shot echo planar imaging readout 72. Note that the echo planar imaging readout is exemplary only, and does not exclude employing additional or other magnetic resonance imaging, magnetic resonance spectroscopy or localized spectroscopy detection schemes. For example, the readout sequence 72 can be a single-shot imaging sequence, a single-shot echo planar sequence, a multi-shot imaging sequence, a spectroscopy sequence, a multiple slice image, a one-dimensional, two-dimensional, or three dimensional spatial encoding sequence, a fractional k-space acquisition sequence, a spin echo readout sequence, a gradient echo readout sequence, or the like.

Looking first at the inversion recovery excitation sequence 70, an inversion pulse 74 is applied to invert the spins. Preferably, the inversion pulse 74 is a 180° pulse implementing a 180° flip angle for the spins. In this case, the inversion time TI 60 is substantially representative to induce proper blood signal reduction based on the T1 value of blood for the particular experimental conditions (field, hematocrit, oxygenation, etc). It is also contemplated, however, to use an inversion pulse having a flip angle greater than 90° but other than 180° , in which case the appropriate inversion time TI 60 is readily computed from the proper T1 and acquisition parameters such as the repetition time TR. In general, the inversion time TI 60 is selected as a time during which the longitudinal component of the flipped spins of blood decay from the flip angle to the crossover or null position. The null condition corresponds to a zero-crossing point of the longitudinal spin component; as the longitudinal spin component decays from the flipped or inverted alignment back toward the normal, non-inverted alignment it passes through a point where the longitudinal component passes substantially through zero, that is, the longitudinal spin component through a substantially zero crossing point. Substantially zero is understood to correspond to a substantially negligible blood signal such that the acquired magnetic resonance signal predominantly contains signals from tissues other than blood.

Preferably, the inversion pulse 74 is not accompanied by a spatial encoding magnetic field gradient pulse or is accompanied by a relatively small spatial encoding magnetic field gradient pulse. This ensures that the spins of blood throughout the subject region of interest reach the null condition after the inversion time delay TI 60. In particular, the blood nulling is independent of blood flow since the blood-nulling inversion pulse 74 is spatially non-selective or selects a relatively large region. Thus, flowing blood that flows into the slice of interest at the time of excitation or at the time of readout is nulled appropriately.

At the blood null condition, that is, after a delay time corresponding to the inversion time TI 60, an excitation pulse 80 is applied in conjunction with a slice-selective magnetic field gradient pulse 82 to excite spins in a selected slice of the subject region of interest. The excitation pulse 80 is preferably a 90° excitation pulse having a flip angle of 90° ; however, an excitation pulse with other than a 90° flip angle is also contemplated. Because the blood is in a null condition at the time the excitation pulse 80 is applied, negligible magnetic resonance signal is excited in the nulled blood by the excitation pulse 80. Tissue such as fat, gray and white brain tissues, and the like generally have a different T1 value from that of blood, and so these tissues are not at a null condition at the time the excitation pulse 80 is applied. Hence, the excitation pulse 80 excites magnetic resonance predominantly in tissue.

The exemplary single shot echo planar imaging readout 72 samples the magnetic resonance excited in the tissue by the excitation pulse 80. The illustrated single shot

echo planar imaging readout 72 is a conventional readout including a 180° spin refocusing radio frequency pulse 84 and slice-selective gradient pulse 86 that create a spin echo in a selected slice at a time-to-echo interval TE after the excitation pulse 80. A series of phase-encoding magnetic field gradient pulses 88 and a generally sinusoidal read magnetic field gradient waveform 90 step through a grid of k-space values in the selected slice while the radio frequency receiver 36 of FIGURE 1 performs sampling 92 of the spin echo. The magnetic resonance signal k-space samples are stored in the k-space memory 40 of FIGURE 1 and are processed to produce a reconstructed image representation as described previously.

The single shot echo planar imaging readout 72 shown in FIGURE 2 is exemplary only. Substantially any type of magnetic resonance imaging or magnetic resonance spectroscopy readout or acquisition sequence can be employed. For imaging applications, the readout sequence may be a fast, single-shot sequence that acquires at least one slice per excitation. For example, the exemplary single shot echo planar imaging readout 72 can be replaced by a short gradient echo readout sequence. An echo time (TE) of the readout shown in FIGURE 2 is preferably kept short so that the readout is performed while the blood remains substantially in the nulled condition and to minimize contributions such as those from the blood-oxygen-level-dependent (BOLD) effect. Optionally, one or more additional inversion pulses are applied to keep the blood close to the null condition during longer readout sequences.

Although the inversion recovery blood-nulling sequence 70 is preferred, other pulse sequences can be employed to substantially null the blood signal so that the magnetic resonance is predominantly due to tissues other than blood. For example, the use of a long echo time (TE) at high magnetic field produces a substantially blood-nulled signal; however, in sequences of this type the extravascular blood oxygenation level dependence (BOLD) contribution is large, complicating determination of other physiological parameters such as cerebral blood volumes (CBV) and the like. In one suitable approach for overcoming this large BOLD effect, the CBV contribution is quantified from interpolation of the TE dependence from a series of TE values at sufficiently long TE to avoid intravascular contributions that would occur at shorter TE and/or from differences between such interpolations under different physiological conditions or between normal and diseased tissue.

The blood-nulling magnetic resonance sequence of FIGURE 2 is optionally repeated with a repetition time (TR) to acquire reconstructed images for multiple slices or for multiple three-dimensional (3D), two-dimensional (2D), or one-dimensional (1D) spatial encodings, for example to obtain a three-dimensional reconstructed image volume. In FIGURE 2, an exemplary succeeding spatially non-selective inversion recovery pulse 74' corresponds to the beginning of the next repetition of the blood-nulling imaging sequence.

Optionally, because the blood nulling establishes a substantially negligible blood signal, it is possible to acquire multiple slices or multiple 1D, 2D, or 3D spatial encodings per single nulling condition. This applies to both imaging and spectroscopy applications.

Reconstructed images acquired using inversion-recovery blood-nulling magnetic resonance sequences such as the exemplary sequence of FIGURE 2 can be used in various ways. For example, while it is known in the art to process a reconstructed image to determine proton density (ρ), T1, and T2 weightings, the determined weighting values are typically composite values having contributions from both blood and tissue. By applying substantially the same processing to the blood-nulled reconstructed images, more accurate ρ , T1, and T2 weightings for tissue can be obtained without interference from the blood signal. Optionally, other tissues are nulled in addition to blood, to minimize contributions from those other tissues or components. For example, such combined blood and tissue nulling can be used to largely isolate a magnetic resonance signal from cerebral spinal fluid (CSF) in the brain.

Reconstructed images acquired using inversion-recovery blood-nulling magnetic resonance sequences contain information pertaining to vascular space occupancy insofar as the images includes contributions from tissue but substantially exclude contributions from the blood volume. By applying a physiological perturbation, the blood volume can be changed. For example, cerebral blood volume undergoes vasodilation responsive to visual stimulation and breath-hold. Similarly, cerebral blood volume undergoes vasoconstriction responsive to hyperventilation. Blood volume changes can also be induced by administration of a selected drug, for example, but not limited to, for stress testing or the assessment of vascular compliance. Moreover, certain diseases such as cardiac ischemia, stroke, cancer, vascular deformations, and the like, represent a chronic or transient physiological perturbation that can cause a change in blood volume detectable with the methodology described herein.

In most of the above cases, the change in blood volume occurs principally in the microvessels rather than in the large vessels and parenchyma. Advantageously, the blood volume changes measured using the blood-nulled reconstructed images reflect the parenchymal blood volume (denoted BV herein) which substantially corresponds to the volume of the microvessels without contributions from the larger vessels. In contrast, vascular volume effects measured by BOLD and many other existing techniques include the large vessels and parenchyma and other tissues close to these vessels (for example, cerebral spinal fluid). For parenchymal tissue (tissue with perfused blood), the parenchymal vascular space occupancy (VASO, also denoted ξ herein) is given by:

$$\xi = \frac{BV}{BV + V_{\text{tissue}}} = \frac{BV}{V_{\text{par}}} \quad (1),$$

where BV is the blood volume, V_{tissue} is the pure tissue volume (without blood), and V_{par} is the volume of the parenchymal tissue, that is, $V_{\text{par}} = BV + V_{\text{tissue}}$. The measured parenchymal vascular space occupancy ξ advantageously is more sensitive to physiological perturbation, including permanent disease-induced perturbation, than is the total vascular volume. Changes in large-vessel volume (that is, outside parenchymal regions) are also accessible by the blood nulling approach. At appropriate resolution, changes in large-vessel volume do not interfere with the indicated parenchymal blood volume changes due to the applied spatial encoding.

For parenchymal tissue, the magnetic resonance signal (denoted by S herein) is proportional to a sum of the magnetization contributions of the microvessels and of the pure tissue. In general, the total signal S_{par} from the parenchymal tissue (including both tissue and perfused blood) can be written as:

$$S_{\text{par}} = S_{\text{blood}} + S_{\text{tissue}} \quad (2),$$

where S_{blood} and S_{tissue} are the blood and tissue signals, respectively. Inserting the vascular space occupancy ξ and water density factors C_{par} and C_{blood} for parenchymal tissue and blood, respectively, into Equation (2) yields:

$$S_{\text{par}} \cong C_{\text{blood}} \cdot \xi \cdot M_{\text{blood}} \cdot e^{-TE/T2_{\text{blood}}} + (C_{\text{par}} - \xi \cdot C_{\text{blood}}) \cdot M_{\text{tissue}} \cdot e^{-TE/T2_{\text{tissue}}} \quad (3),$$

where $T2_{\text{blood}}$ and $T2_{\text{tissue}}$ are suitable time constants for the exemplary spin echo readout of FIGURE 2 due to the spin refocusing produced by the radio frequency pulse 84. For a gradient echo readout, the T2 values should be replaced by T2* values in Equation (3). The terms M_{blood} and M_{tissue} correspond to the initial transverse magnetization of the blood and the tissue, respectively, produced by the excitation radio frequency pulse 80. As a consequence of using the blood-nulling excitation sequence 70, however, the term M_{blood} corresponding to the blood is substantially zero, and so Equation (3) reduces to:

$$S_{\text{par}} \cong (C_{\text{par}} - \xi \cdot C_{\text{blood}}) \cdot M_{\text{tissue}} \cdot e^{-TE/T2_{\text{tissue}}} \quad (4).$$

A fractional parenchymal signal change $\Delta S/S$ occurring responsive to a physiological perturbation, defined as:

$$\frac{\Delta S}{S} = \frac{S_{\text{par}}^{\text{act}} - S_{\text{par}}^{\text{rest}}}{S_{\text{par}}^{\text{rest}}} \quad (5),$$

5

can be written by combining Equations (4) and (5) as:

$$\frac{\Delta S}{S} = \frac{(C_{\text{par}} - \xi^{\text{act}} \cdot C_{\text{blood}}) \cdot e^{-TE/T2_{\text{tissue}}^{\text{act}}} - (C_{\text{par}} - \xi^{\text{rest}} \cdot C_{\text{blood}}) \cdot e^{-TE/T2_{\text{tissue}}^{\text{rest}}}}{(C_{\text{par}} - \xi^{\text{rest}} \cdot C_{\text{blood}}) \cdot e^{-TE/T2_{\text{tissue}}^{\text{rest}}}} \quad (6),$$

10

where the superscript "act" references the perturbed state and the superscript "rest" references the unperturbed rest state or another suitable reference state. Dividing the numerator and denominator of Equation (6) by $C_{\text{par}} e^{-TE/T2_{\text{tissue}}^{\text{rest}}}$, the fractional parenchymal signal change $\Delta S/S$ can be written as:

$$\frac{\Delta S}{S} = \frac{(1 - \xi^{\text{act}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}) \cdot e^{-TE/(1/T2_{\text{tissue}}^{\text{act}} - 1/T2_{\text{tissue}}^{\text{rest}})} - (1 - \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}})}{(1 - \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}})} \quad (7),$$

15

Making use of the series expansion approximation $e^x \sim 1+x$ and defining an apparent change in transverse relaxation rate of tissue $\Delta R2$ as:

$$\Delta R2 = \frac{1}{T2_{\text{tissue}}^{\text{act}}} - \frac{1}{T2_{\text{tissue}}^{\text{rest}}} \quad (8),$$

20

Equation (7) can be rewritten as:

$$\frac{\Delta S}{S} = \frac{-\Delta R2 \cdot TE - \xi^{\text{act}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}} + \xi^{\text{act}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}} \cdot \Delta R2 \cdot TE + \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}}{(1 - \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}})} \quad (9).$$

25

Defining a rate of change $\Delta\xi$ of the vascular space occupancy as $\Delta\xi = \xi^{\text{act}} - \xi^{\text{rest}}$ and neglecting the term $\xi^{\text{act}} (C_{\text{blood}}/C_{\text{par}}) \Delta R2 \text{ TE}$ in Equation (9) and simplifying yields:

$$\frac{\Delta S}{S} = \frac{-\Delta R2 \cdot \text{TE} - \Delta\xi \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}}{(1 - \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}})} \quad (10).$$

5

FIGURE 3 shows a block diagram of an exemplary processor 100 that computes a rest blood volume BV^{rest} and a blood volume change ΔBV based on Equation (10). The processor 100 receives imaging data input from the image memory 46. The imaging data includes images taken at a plurality of echo times TE 102 with the imaging subject at rest, and corresponding images taken at the plurality of (that is, two or more) echo times TE with the imaging subject in a perturbed state. A processor 104 computes the fractional signal difference $\Delta S/S$ between the image of the subject in the rest state and the image of the subject in the perturbed state for each echo time TE to form a table 106 of fractional signal difference $\Delta S/S$ versus echo time TE. Recognizing that Equation (10) is a linear equation in echo time TE, a linear regression processor 110 computes a slope 112 and an ordinate-intercept 114 of the $\Delta S/S$ v. TE relationship.

15

A rest blood volume BV^{rest} calculator 116 computes the rest blood volume BV^{rest} 118 from the slope 112 according to:

20

$$\text{slope} = \frac{-\Delta R2}{1 - \xi^{\text{rest}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}} = \frac{-\Delta R2}{1 - \frac{BV^{\text{rest}}}{V_{\text{par}}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}} \quad (11),$$

25

where Equation (11) is the slope component of the linear relationship between $\Delta S/S$ and TE of Equation (10). The rightmost side of Equation (11) is written with the rest parenchymal vascular space occupancy ξ^{rest} replaced by blood volume BV^{rest} divided by the volume V_{par} of the parenchymal tissue under consideration in accordance with Equation (1). The BV^{rest} calculator 116 uses literature values for the water density factors C_{par} and C_{blood} , the known volume V_{par} of the parenchymal tissue under consideration, and a value for $\Delta R2$ calculated from $T2_{\text{tissue,act}}$ and $T2_{\text{tissue,rest}}$ values obtained by fitting the signal value S at several echo times TE for each of the perturbed and rest states, respectively. If V_{par} is unknown, the method can be used to determine the absolute blood volume fraction or vascular space occupancy (ξ^{rest}).

30

A blood volume change ΔBV calculator 122 computes the blood volume rate of change ΔBV 124 from the ordinate-intercept 114 according to:

$$\text{Intercept} = \frac{-\left(\frac{\Delta BV}{V_{\text{par}}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}\right)}{\left(1 - \frac{BV^{\text{rest}}}{V_{\text{par}}} \cdot \frac{C_{\text{blood}}}{C_{\text{par}}}\right)} \quad (12),$$

5

where Equation (12) is the ordinate-intercept component of the linear relationship between $\Delta S/S$ and TE of Equation (10) written with the rest parenchymal vascular space occupancy ξ^{rest} replaced by $BV^{\text{rest}}/V_{\text{par}}$ and the change in vascular space occupancy $\Delta \xi$ is replaced by $\Delta BV/V_{\text{par}}$. The ΔBV calculator 122 uses literature values for the water density factors C_{par} and C_{blood} , the known volume V_{par} of the parenchymal tissue under consideration, and the rest blood volume BV^{rest} 118 computed by the BV^{rest} calculator 116. Alternatively, the absolute blood volume fraction or vascular space occupancy (ξ^{rest}) can be used if V_{par} is unknown.

FIGURE 4 shows a block diagram of another processor 130 that computes an absolute blood volume BV . Computation of BV by the processor 130 is not based on a transient response to a physiological perturbation. Rather, data from the image memory 46, which may be a single image, is processed using Equation (4). The image is preferably acquired using a short echo time TE , so that the term $\exp(-TE/T2_{\text{tissue}})$ in Equation (4) is suitably approximated as unity so that the signal S is given by:

$$S_{\text{par}} \cong \left(C_{\text{par}} - \frac{BV}{V_{\text{par}}} \cdot C_{\text{blood}}\right) \cdot M_{\text{tissue}} \quad (13),$$

where the parenchymal vascular space occupancy ξ is replaced by the expression in Equation (1). The value of M_{tissue} at the inversion time TI 60 is related to longitudinal tissue relaxation time $T1_{\text{tissue}}$ according to:

25

$$M_{\text{tissue}}(TI) = 1 - 2e^{-TI/T1_{\text{tissue}}} + e^{-TR/T1_{\text{tissue}}} \quad (14),$$

where TR is the repetition time of the pulse sequence (indicated, for example, in FIGURE 2). A suitable value for $T1_{\text{tissue}}$ can be measured using a known magnetic resonance technique such as saturation recovery pulse sequence and inversion recovery pulse sequence or, preferably, by

30

a series of inversion pulses so that blood remains substantially nulled, while tissue signal decays with the representative $T1_{\text{tissue}}$. In the case of brain imaging, it is known that the $T1_{\text{tissue}}$ values for white and gray brain matter differ. Hence, as shown in FIGURE 4 a $T1_{\text{white}}$ value 132 and a $T1_{\text{gray}}$ value 134 are preferably determined. Notice that S_{par} also contains instrumental factors, for instance related to coil sensitivity and excitation homogeneity, the combined contribution of which we will call IF. This constant can also be determined during the $T1$ measurement from the voxels in ventricles, which only contains CSF and has a proton density very close to pure water. An M_{tissue} processor 136 computes corresponding M_{tissue} values at the inversion time TI 60 for white and gray brain matter, and a normalization processor 140 normalizes the image stored in the image memory 46 to produce a normalized image 142 according to:

$$S_{\text{norm}}(\text{tissue}) = \frac{S_{\text{par}}}{\text{IF} \cdot M_{\text{tissue}}} \quad (15),$$

where in Equation (15) the tissue magnetization M_{tissue} is selected as the magnetization term corresponding to the $T1_{\text{gray}}$ value 134 for gray matter, and is selected as the magnetization term corresponding to the $T1_{\text{white}}$ value 136 for white matter. A blood volume processor 144 estimates the absolute blood volume BV 146 or the absolute blood volume fraction or vascular space occupancy (ξ^{rest}) by applying Equation (13) to the normalized image 142. For pure parenchyma, an additional approach to determine blood volume is to use the tissue $T1$ value to null the tissue and only look only at remaining blood. Using the same IF determined in the blood nulling experiment, the signal in such a tissue-nulled voxel at short TE is given by:

$$S_{\text{norm}}(\text{blood}) = \frac{S_{\text{par}}}{\text{IF} \cdot M_{\text{blood}}} = C_{\text{blood}} \cdot \xi \quad (16)$$

25

from which the BV (Equation (1)) and/or vascular space occupancy can be determined for known C_{blood} .

FIGURE 5 shows a processor 150 that computes a clinical image from blood-nulled magnetic resonance images. The processor 150 is suitable in diagnostic applications for detecting an abnormality such as vasodilation or vasoconstriction caused by certain diseases such as cardiac ischemia, stroke, cancer, and the like. The image memory 46 stores an image of the imaging subject to be diagnosed. The image is compared with a reference image 152 by a difference processor 154 to generate a clinical image 156.

30

In one suitable approach, the difference processor 154 computes an absolute difference between the images, so that normal areas appear dark in the clinical image 156 whereas abnormal areas appear brighter in the clinical image 156 (or vice versa) due to differences between the subject image and the reference image in the vicinity of the abnormality. Optionally, the difference processor 154 computes a signed difference with a constant intensity level offset. In this approach, regions of vasodilation and regions of vasocontraction have opposite intensity polarities respective to the constant intensity level.

The reference image 152 can be obtained from various sources. For example, an image of a normal subject can be employed for the comparison. Alternatively, in the case of a bilaterally symmetric anatomical structure such as the brain, a contralateral image can be used. For example, a suspect right-side of the brain can be compared with a presumed normal left-side of the brain, preferably after a suitable left-right transposition of the contralateral comparison image. Still further, in cases of anatomical structures that are substantially homogeneous in the absence of an abnormality, a suspect portion of the organ can be compared with presumed normal portion of the same organ.

In the case of brain diagnoses, the normalized image 142 of FIGURE 4 is optionally employed in the processor 150. The normalized image 142 advantageously has suppressed contrast between white matter regions and gray matter regions of the brain image, which makes the vascular space occupancy contrast more visible.

In some clinical applications, large vessels changes may occur in addition to microvascular changes. These can also be detected, and, at sufficient spatial resolution, can be separated from the microvascular changes.

The invention has been described with reference to the preferred embodiments. Obviously, modifications and alterations will occur to others upon reading and understanding the preceding detailed description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

Claims

Having described the preferred embodiments, the invention is now claimed to be:

1. A magnetic resonance method including:

performing a blood-nulling magnetic resonance excitation sequence (70) that substantially nulls a magnetic resonance signal from blood; and

subsequent to the performing of the blood-nulling magnetic resonance excitation sequence (70), performing a readout magnetic resonance sequence (72) to acquire a magnetic resonance signal from tissue other than the nulled blood.

2. The magnetic resonance method as set forth in claim 1, wherein the performing of a blood-nulling magnetic resonance sequence (70) includes:

performing an inversion recovery magnetic resonance excitation sequence (70) having an inversion time (60) to substantially null the magnetic resonance signal from blood.

3. The magnetic resonance method as set forth in claim 2, wherein the performing of an inversion recovery magnetic resonance sequence (70) includes:

applying an inversion radio frequency pulse (74);

delaying for the inversion time (60); and

applying an excitation radio frequency pulse (80).

4. The magnetic resonance method as set forth in claim 3, wherein:

the applying of the inversion radio frequency pulse (74) is performed without an accompanying spatially selective magnetic gradient pulse; and

the applying of the excitation radio frequency pulse (80) is performed with an accompanying spatially selective magnetic field gradient pulse (82).

5. The magnetic resonance method as set forth in claim 3, wherein the performing of an inversion recovery magnetic resonance sequence (70) further includes:

applying additional inversion radio frequency pulses to maintain blood in a substantially nulled condition.

6. The magnetic resonance method as set forth in claim 3, wherein the inversion radio frequency pulse (74) is a 180° pulse and the excitation radio frequency pulse (80) is a 90° pulse.

7. The magnetic resonance method as set forth in claim 2, further including determining the inversion time (60) for nulling blood by:

determining a T1 value of blood; and

selecting the inversion time (60) for substantial blood nulling based on the determined T1 value of blood.

8. The magnetic resonance method as set forth in claim 7, wherein the determining of a T1 value of blood includes:

acquiring a representative blood sample; and

measuring the T1 value of the representative blood sample.

9. The magnetic resonance method as set forth in claim 7, wherein the determining of a T1 value of blood further includes:

determining a hematocrit of the blood; and

correcting the T1 value of blood for the determined hematocrit.

10. The magnetic resonance method as set forth in claim 2, further including:
identifying at least a main magnetic field strength and a repeat time; and
determining the inversion time (60) for nulling blood based on a predetermined relationship (64) between the inversion time for nulling the blood and the identified main magnetic field strength and repeat time.

11. The magnetic resonance method as set forth in claim 2, further including:
optimizing an inversion time of a calibration inversion recovery magnetic resonance excitation sequence to minimize a magnetic resonance signal of a large blood vessel; and
selecting (66) the inversion time (60) for nulling blood as the optimized inversion time of the calibration inversion recovery magnetic resonance excitation sequence.

12. The magnetic resonance method as set forth in claim 2, further including:
generating a reconstructed image from the acquired magnetic resonance signal.

13. The magnetic resonance method as set forth in claim 12, further including:
subsequent to performing the readout magnetic resonance sequence, inducing a physiological perturbation;
subsequent to inducing the physiological perturbation, repeating performing the inversion recovery magnetic resonance excitation sequence (70) and performing the readout

magnetic resonance sequence (72) to acquire a second magnetic resonance signal from tissue other than the nulled blood; and

generating a perturbation reconstructed image from the acquired second magnetic resonance signal.

14. The magnetic resonance method as set forth in claim 12, further including:

subsequent to performing the readout magnetic resonance sequence (72), inducing a physiological perturbation;

subsequent to inducing the physiological perturbation, repeating performing the inversion recovery magnetic resonance excitation sequence (70);

subsequent to repeating the performing of the inversion recovery magnetic resonance excitation sequence (70), performing a plurality of readout magnetic resonance sequences (72) each having a different echo time to acquire a plurality of magnetic resonance signals corresponding to the plurality of echo times;

generating a plurality of perturbation reconstructed images from the acquired plurality of magnetic resonance signals corresponding to the plurality of echo times; and

determining a temporal evolution of a physiological response to the physiological perturbation based on the plurality of perturbation reconstructed images.

15. The magnetic resonance method as set forth in claim 14, wherein the determining of a temporal evolution includes:

computing a change in vascular space occupancy signal between perturbation reconstructed images and corresponding unperturbed reconstructed images for each echo time to produce change in vascular space occupancy signal versus echo time data (106); and

fitting the change in vascular space occupancy signal versus echo time data (106) to a mathematical model to obtain a blood volume parameter value (118).

16. The magnetic resonance method as set forth in claim 12, further including:

determining a T1 value of tissue (132, 134);

computing a tissue magnetization (M) based on the T1 value of the tissue (132, 134);

generating a normalized reconstructed image (142) by dividing the reconstructed image by the tissue magnetization; and

estimating a blood volume parameter value (146) based on the normalized reconstructed image (142).

17. The magnetic resonance method as set forth in claim 16, wherein the reconstructed image corresponds to a subject brain region, and determining the T1 value of the tissue (132, 134) includes:

determining a first T1 value (132) corresponding to white brain matter; and

determining a second T1 value (134) corresponding to gray brain matter;

wherein the dividing of the reconstructed image by the tissue magnetization uses for each image element a selected one of the first and second T1 values (132, 134) based on a classification of local tissue type as one of gray brain matter and white brain matter.

18. The magnetic resonance method as set forth in claim 12, wherein performing the readout magnetic resonance sequence (72) effects imaging of a subject brain region of a subject brain, and the method further includes:

providing a reference image (152) of a reference brain region; and

comparing the reconstructed image with the reference image (152) to detect an abnormality of the subject brain region.

19. The magnetic resonance method as set forth in claim 18, wherein providing the reference image (152) of a reference brain region includes repeating:

performing the inversion recovery magnetic resonance excitation sequence (70),

performing the readout magnetic resonance sequence (72), and

generating the reconstructed image on the reference brain region to generate the reference image (152).

20. The magnetic resonance method as set forth in claim 19, wherein the reference brain region is selected from a group consisting of:

a brain region of a contralateral side of the subject brain corresponding to the subject brain region,

a brain region of a brain other than the subject brain which corresponds to the subject brain region, and

a brain region of the subject brain other than the subject brain region.

21. The magnetic resonance method as set forth in claim 12, further including:

computing at least one of a proton density weighting of tissue, a T1 weighting of tissue, and a T2 weighting of tissue without interference from a magnetic resonance signal of blood based on the reconstructed image.

22. The magnetic resonance method as set forth in claim 2, wherein performing the readout magnetic resonance sequence (72) includes performing one or more of:

- a single-shot imaging sequence,
- a single-shot echo planar sequence,
- a multi-shot imaging sequence,
- a spectroscopy sequence,
- a multiple slice image,
- a one-dimensional, two-dimensional, or three dimensional spatial encoding sequence,
- a fractional k-space acquisition sequence,
- a spin echo readout sequence, and
- a gradient echo readout sequence.

23. A magnetic resonance system including:

a blood nulling means (10, 12, 16, 18, 30, 32, 34) for performing a blood nulling magnetic resonance excitation sequence (70) that substantially nulls a magnetic resonance signal from blood; and

a readout means (10, 12, 16, 18, 30, 32, 36) for performing a readout magnetic resonance sequence (72) to acquire a magnetic resonance signal from tissue other than the nulled blood, the readout means (10, 12, 16, 18, 30, 32, 36) operating subsequent to operation of the blood nulling means (10, 12, 16, 18, 30, 32, 34).

24. The magnetic resonance system as set forth in claim 23, wherein the blood nulling means (10, 12, 16, 18, 30, 32, 34) includes:

an inversion recovery means (10, 12, 16, 18, 30, 32, 34) for performing an inversion recovery magnetic resonance excitation sequence (70) having an inversion time (60) in which magnetic resonance of blood is substantially nulled.

25. The magnetic resonance system as set forth in claim 24, further including:

a means (64) for determining the inversion time (60) based on a set of values including at least a magnetic field strength value and a repeat time value.

26. The magnetic resonance system as set forth in claim 24, further including:

a means (62) for measuring a T1 value of blood, the inversion time (60) being obtained from the measured T1 value of blood.

27. The magnetic resonance system as set forth in claim 24, further including:

a reconstruction means (44) for generating a reconstructed image from the acquired magnetic resonance signal.

28. The magnetic resonance system as set forth in claim 27, further including:

a means (100, 130) for computing a blood volume parameter value (118, 146) from the reconstructed image.

29. The magnetic resonance system as set forth in claim 28, wherein the means (130) for computing a blood volume parameter value (118, 146) includes:

a means (136, 140) for normalizing the reconstructed image based on a T1 value of tissue (132, 134) to generate a tissue-normalized reconstructed image; and

a means (144) for computing the blood volume from the tissue-normalized reconstructed image.

30. The magnetic resonance system as set forth in claim 28, wherein the means (100) for computing a blood volume parameter value (118, 146) includes:


a means (104) for computing an intermediate parameter (106) functionally related to blood volume for a plurality of reconstructed images produced by repetitively invoking the readout means and the reconstruction means with a corresponding plurality of echo times (102); and


a means (110) for fitting a parameterized model to the intermediate parameters (106) and the corresponding echo times (102), the parameterized model having parameters including a rest blood volume (118) and a blood volume change (124).

31. The magnetic resonance system as set forth in claim 27, further including:

a means (154) for combining the reconstructed image with a reference image (152) to identify an abnormality in the reconstructed image.

1 / 5





3 / 5





FIG 3

4 / 5



5 / 5




FIG 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/26580

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01R33/563 A61B5/026 A61B5/055

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01R A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 221 899 A (GONEN ODED ET AL) 22 June 1993 (1993-06-22) abstract; claim 1	1-31
A	US 4 942 359 A (SANO KOICHI ET AL) 17 July 1990 (1990-07-17) column 3, line 5 -column 4, line 45; claim 1	1-31
A	EP 0 297 832 A (BRITISH TECH GROUP) 4 January 1989 (1989-01-04) the whole document	1-31

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

8 document member of the same patent family

Date of the actual completion of the international search

10 December 2003

Date of mailing of the international search report

18/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Chopinard, M

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/26580

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5221899	A	22-06-1993	NONE	
US 4942359	A	17-07-1990	JP 1192342 A JP 2595006 B2 DE 3902490 A1	02-08-1989 26-03-1997 10-08-1989
EP 0297832	A	04-01-1989	DE 3855320 D1 DE 3855320 T2 EP 0297832 A2 GB 2206970 A , B JP 1259849 A JP 2677386 B2 US 4906932 A	04-07-1996 02-10-1996 04-01-1989 18-01-1989 17-10-1989 17-11-1997 06-03-1990

BEST AVAILABLE COPY